

VAKUUM TAMBLER 8.750 ltr

VACUUM TUMBLER 8.750 ltr



LINIJSKA PROIZVODNJA

Vakuum tambleri serije C sa dvoja vrata posebno su pogodni za linijsku proizvodnju jer se otvori za punjenje i pražnjenje nalaze na suprotnim stranama.

Robustan pogon preko 4 posebna točka za velika opterećenja i frekventno regulisan prenos omogućavaju brzinu od 1 - 10 o/min. Dvoja vrata omogućavaju brzo punjenje, pražnjenje i čišćenje.

LINIJSKA PRODUCTION

The double-doored vacuum tumbler of our Production Line C are especially suited for "in line" production, since the lid openings for loading and discharge of the product are in opposite directions.

A robust drive with four heavy-duty wheels and a frequency controller allow a speed range between 1 and 10 RPM. The opposing opening lids enable fast loading and discharge as well as thorough cleaning.





- Robusna konstrukcija sa precizno izrađenim bubnjem
- Pogon preko posebnih točkova za velika opterećenja
- Frekventno regulisan broj obrtaja
1 - 10 o/min
- Posebne lopatice za kontrolisano okretanje, klizanje
i pomeranje proizvoda
- Svi parametri masiranja mogu se
programirati preko jednostavnog Siemens ekrana
slobodno
na dodir
- Uređaj za usisavanje dodatne salamure
i/ili aditiva
- Vakuum 95%
- Punjenje: 5- 50% (zavisno od proizvoda)



- sturdy construction with precision drum
- drive by four heavy-duty wheels
- frequency controlled rotational speed, ranging from
1 to 10 RPM
- special fins for controlled turning, slide and glide
movements
- all tumbler parameters can be adjusted by the user
friendly SIEMENS touch panel and are also
programmable
- vacuum brine suction device for extra brine and
additives
- 95 % vacuum
- loading capacity: 5 - 50% (product-dependent)

Tip type	Zapremina volume	Broj obrtaja rpm	Snaga power	Širina width	Dužina length	Visina height
C5	8.750 ltr	1-10	21,0 kW	2.810 mm	3.280 mm	2.650 mm