

## INJEKTOR SALAMURE HPI 300

### BRINE INJECTOR HPI 300



24

igle  
needles

Važna karakteristika modela HPI 300 je podesiva pritisna ploča. Može se zaustaviti iznad proizvoda ili osloniti na njega. Moguće je ubrizgavanje u proizvode sa kostima i bez kostiju.

A very important feature of the HPI 300 is the flexible adjustment if the stripper plate. It can optionally stop above the product or hit the product. You can inject products with or without bones.



- Transport češljem
- Kompaktna konstrukcija
- Robusna izrada
- Pojedinačno opruženje igala
- Jednostavno održavanje i čišćenje
- Prinudno ubrizgavanje kontrolisano pritisnom pločom
- Dovod salamure preko centralnog ventila
- Samousisna centrifugalna pumpa od inoksa
- Promena rasporeda uboda (polovični / puni hod transportnog češlja)
- Automatski prekid dotoka salamure u pojedinačne igle pri dodiru kosti

## HPI 300

Radna širina /  
working width 300

Pomak u mm/hodu  
advance in mm/stroke 15/30

Broj igala, jedna glava  
quantity of needles injector  
with single head 24

Broj igala, dve glave  
quantity of needles injector  
with double head --

Transportni sistem /  
transport system Češalj od inoksa  
walking beam

Visina hoda u mm /  
stroke height in mm 200

Pritisak salamure u bar /  
brine pressure in bar 0,5 - 4

Brzina hoda /  
stroke speed 50

Priključna snaga u kW  
connection power in kW 2

Dužina u mm /  
length (mm) 1.510

Širina u mm /  
width (mm) 700

Visina u mm /  
height (mm) 1.930

Masa u kg / weight (kg) 380