

INJEKTOR SALAMURE HPI 350

BRINE INJECTOR HPI 350

HPI 350 je osnovni model industrijskih injektora. Brzina se podešava od 15-55 hodova/min.

Za HPI 350 dostupne su brojne opcije: ekran na dodir, bazen za salamuru, jedinica protiv taloženja, dvocevni izmenjivač toplote i druge, za prilagođavanje sopstvenom proizvodnom procesu.

The HPI 350 is the starter model at the industrial injectors for small and middle capacities. The speed is adjustable from 15-55 strokes per minute.

At the HPI 350 the customer can already choose from a variety of options like Touch Panel, brine pool, antisedimentation unit, double pipe heat exchanger and many more to adapt the machine to their own requirements and production processes.



50/102

igle
needles

- beam walk
- Compact construction
- Sturdy manufacturing
- Single needle springing
- Easy to maintain, easy to clean
- Forced injection controlled by stripper plate
- Brine feeding with central valve
- Self-priming stainless steel pump
- Changing of stitch pattern (half or full draw of transport system)
- Automatic brine stop of single needles after contact with bones



HPI 350

Radna širina /
working width 350

Pomak u mm/hodu
advance in mm/stroke 30/60

Broj igala, jedna glava
quantity of needles injector
with single head 50 ili 102

Broj igala, dve glave
quantity of needles injector
with double head --

Transportni sistem /
transport system Češalj od inoksa
walking beam

Visina hoda u mm /
stroke height in mm 200 / 230

Pritisak salamure u bar /
brine pressure in bar 0,5 - 4

Brzina hoda /
stroke speed 15 - 55

Priključna snaga u kW
connection power in kW 8

Dužina u mm /
length (mm) 1.920

Širina u mm /
width (mm) 1.140

Visina u mm /
height (mm) 2.050

Masa u kg / weight (kg) 460